



## Elite Series

Blanket Warming Cabinets

**Temperature Range**  
98°F - 180°F (37°C - 82°C)

**Energy Consumption**  
Efficient, balanced control allows for low energy use and minimal heat loss.

**Radiant Heat Technology**  
Utilizes multiple zone heating that monitors surfaces for safe temperature ranges.

**Interior Lighting**  
Casts a comforting blue glow with two (2) different intensity settings.

**Epoxy-Coated**  
interior surfaces

**Three cabinet sizes**  
available.

*featuring*

**RADIANT HEAT  
TECHNOLOGY**



**P-2220 • P-2210 • P-2205**

**Specifications:**

- Single-chamber warming cabinet.
- White epoxy-coated steel interior insert and exterior casing.
- Single pane energy efficient e-coated glass window door allows inventory observation.
- Easy, hands-free door release.
- Door is fully gasketed and hinged on the right side of the unit.
- Four (4) ¾" non-skid rubber feet.
- Radiant Heat Technology utilizes multiple zone heating that monitors surfaces for safe temperature ranges.
- P-2220 includes a heated center shelf.

**Control:**

- Electronic control.
- Efficient, balanced heating system allows for low energy consumption and minimal heat loss.
- Adjustable temperature range of 98°F - 180°F (37°C - 82°C).
- Operate in Fahrenheit or Celsius.
- Four digit L.E.D. display.
- On/Off key.
- Actual temperature key.
- Increase and decrease keys.
- Built-in speaker for audible feedback.
- Built-in control button lock-out feature.

**Additional features:**

- L.E.D. interior lighting casts a comforting blue glow with two (2) different intensity settings and off mode.
- In the event of a power failure, the cabinet will remember its programming and begin to operate as before when power is restored.
- A warming shut-off system, separate from the electronic control, prevents overheating.
- Optional timer key allows the user to program the control to automatically turn on and off at a selected time.



Model	P-2205	P-2210	P-2220
Interior Capacity	1.5 ft <sup>3</sup>	2.5 ft <sup>3</sup>	3.5 ft <sup>3</sup>
Net Weight	56 lbs (25 kg)	67 lbs (30 kg)	91 lbs (41 kg)
Ship Weight	58 lbs (26 kg)	135 lbs (61 kg)	167 lbs (76 kg)
<b>Electrical</b>			
120V Amps	5.0	5.0	6.7
120V kW	0.6	0.6	0.8
Plug (Hospital Grade)	NEMA 5-15P; 15A-125V Plug	NEMA 5-15P; 15A-125V Plug	NEMA 5-15P; 15A-125V Plug
220V Amps	2.7 (Plug - contact factory)	2.7 (Plug - contact factory)	3.6 (Plug - contact factory)
220V kW	0.6 (Plug - contact factory)	0.6 (Plug - contact factory)	0.8 (Plug - contact factory)
230V Amps	2.6	2.6	3.4
230V kW	0.6	0.6	0.8
Plug	BS 1363 Plug (UK only)	BS 1363 Plug (UK only)	BS 1363 Plug (UK only)
	CEE 7/7, 220-230V Plug	CEE 7/7, 220-230V Plug	CEE 7/7, 220-230V Plug

